



# DVR 5IN1 SYSTEM

AHD /TVI /CVI /CVBS /IPC SYSTEM SUPPORT

# H.265

# 5MPiXEL

Video Recorder



## DVR 7500 SERIES



# DVR 5IN1 SYSTEM

AHD /TVI /CVI /CVBS /IPC SYSTEM SUPPORT

## Specification

**5MPiXEL HD**  
Video Recorder



## Feature

- \* Analog video-input 4CH inputs
- \* IP Video Input 2ch,(only IP up to 6ch)
- \* Composite Video Input up to 6 ch (Analog video + IP video)
- \* Compression Audio: G.711a / Video: H.264 / H.265
- \* Playback 5MPlite: 48fps  
4MPlite: 64fps  
1080P: 60fps (Max 4CH playback)  
720P: 120fps (Max 4CH playback)
- \* Ethernet 1 RJ45 10/100 Base-T
- \* USB2.0\*1(front) / USB2.0\*1+(rear)
- \* Audio 4 in / 1 out
- \* HDD1 SATA HDD, up to 8TB
- \* RS485 1
- \* Input Voltage / Current 1HDD: DC12V/2A

# H.265

## DVR 7500 SERIES

Model	HA-75504P-V1
Inputs	8Mbps ~ 24Mbps IP Bandwidth default is 8Mbps, decrease one Analog channel can increase 4Mbps Total decoding performance 1080P 60fps
Out	48 Mbps
Analog video-input	4CH inputs
Live	
IP Video Input	2ch, (only IP up to 6ch)
Composite Video Input	up to 6 ch (Analog video + IP video)
Performance	
Installation wizard	Yes
Recording and Playback	
Compression	Audio: G.711a Video: H.264 / H.265
Display resolution	Analog: 5MP-Lite: 20fps / 4MP-Lite: 30 fps 1080P / 720P / 960H: 30fps IP: 5MP / 4MP / 1080P / 720P Single IP channel preview up to 2MP 30 fps multi-channel preview only substream
Speed	Analog: 5MP-Lite: 12fps (each ch) 4MP-Lite:16fps (each ch) 1080P: 15fps (each ch) 720P: PAL: 25fps (each ch) / NTSC: 30fps (each ch) IP: PAL: 25fps (each ch) / NTSC: 30fps (each ch) Sub-stream Max PAL: 704*576: 10fps (each ch) NTSC: 704*480: 10fps (each ch)
Event	MD (Sensitivity Level 1-8) Videlo loss Beep, Email, Push notification to Mobile APP
Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	5MPlite: 48fps / 4MPlite: 64fps 1080P: 60fps (Max 4CH playback) 720P: 120fps (Max 4CH playback)
UI/Monitoring	
Local	UI5.0
WEB	IE10/11
Mobile viewer	Rxcamview
Push N/Atification	TUTK/RS
P/W Reset	Password Reset: Press 3 seconds Factory Reset: Press 10 seconds BNC 1 (704*576)
Monitors	
VGA	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
HDMI	1 (1024*768,1280*720,1280*1024,1440*900,1920*1080, 2560*1440(2K),3840*2160(4K))
Ethernet	1 RJ45 10/100 Base-T
USB	USB2.0*1 (front) / USB2.0*1+(rear)
Audio	4 in / 1 out
E-sata	0
HDD	1 SATA HDD, up to 8TB
RS485	1
Alarm Input/out	0
General	
OSD Language	More
Dimension (WxDxH)	300X227X53mm
Input Voltage / Current	1HDD: DC12V/2A
Power consumption (excluding hard disk)	3.6W
Operating Temperature	Temperature: 0C~+40C (32F ~ 104F)
Operating Humidity	Humidity: Less than 90%RH"