



DVR 5IN1 SYSTEM

AHD /TVI /CVI /CVBS /IPC SYSTEM SUPPORT

H.265

5M PIXEL

Video Recorder



FULL AUDIO

Support Audio Full channel



DVR 7500 SERIES



DVR 5IN1 SYSTEM

AHD /TVI /CVI /CVBS /IPC SYSTEM SUPPORT

Specification

5MPiXEL HD
Video Recorder



Feature

- * Analog video-input 8CH inputs
- * IP Video Input 4ch, (only IP up to 12ch)
- * Composite Video Input up to 12ch (Analog video + IP video)
- * Compression Audio: G.711a / Video: H.264 / H.265
- * Playback 5MPiLite: 90fps (Max 6CH playback)
4MPiLite: 126fps (Max 7CH playback)
1080P: 120fps (Max 8CH playback)
720P: 240fps (Max 8CH playback)
- * Ethernet 1 RJ45 10/100Base-T
- * USB2.0*1(front) / USB2.0*1+(rear)
- * Audio optional
- * HDD1 SATA HDD, up to 8TB
- * RS485 1
- * Alarm Input / out 8in / 1out
- * Input Voltage / Current 1HDD: DC12V/2A



H.265

FULL AUDIO
Support Audio Full channel

DVR 7500 SERIES

Model	HA-75508P-A-V1
Inputs	16Mbps ~ 48Mbps IP Bandwidth default is 16Mbps, decrease one Analog channel can increase 4Mbps default decoding performance 1080P 60fps decrease one Analog channel can increase 1080P 7fps
Out	64Mbps
Analog video-input	8CH inputs
Live	
IP Video Input	4ch, (only IP up to 12ch)
Composite Video Input	up to 12ch (Analog video + IP video)
Performance	
Installation wizard	Yes
Recording and Playback	
Compression	Audio: G.711a / Video: H.264 / H.265
Display resolution	Analog: 5MP-Lite: 20fps / 4MP-Lite: 30fps 1080P / 720P / 960H: 30fps / IP: 4MP / 1080P / 720P Single IP channel preview up to 2MP 30fps multi-channel preview only substream
Speed	Analog: 5MP-Lite: 15fps (each ch) / 4MP-Lite: 18fps (each ch) 1080P: 15fps (each ch) 720P: PAL: 25fps (each ch) / NTSC: 30fps (each ch) IP: PAL: 25fps (each ch) / NTSC: 30fps (each ch) Sub-stream Max PAL: 704*576: 10fps (each ch) NTSC: 704*480: 10fps (each ch)
Event	MD(Sensitivity Level 1~8) Videlo loss Beep, Email, Push notification to Mobile APP
Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	5MPiLite: 90fps (Max 6CH playback) 4MPiLite: 126fps (Max 7CH playback) 1080P: 120fps (Max 8CH playback) 720P: 240fps (Max 8CH playback)
UI/Monitoring	
Local	UI5.0
WEB	IE10/11
Mobile viewer	Rxcamview
Push N/Atification	TUTK/RS
P/W Reset	Password Reset: Press 3 seconds Factory Reset: Press 8 seconds
Monitors	
BNC	1 (704*576) VGA 1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
HDMI	1 (1024*768,1280*720,1280*1024,1440*900,1920*1080, 2560*1440(2K),3840*2160(4K))
Ethernet	1 RJ45 10/100Base-T
USB	USB2.0*1(front) / USB2.0*1+(rear)
Audio	optional
E-sata	0
HDD	1 SATA HDD, up to 8TB
RS485	1
Alarm Input / out	8 in / 1 out
General	
OSD Language	More
Dimension (WxDxH)	300X227X53mm
Input Voltage / Current	1HDD: DC12V/2A
Power consumption (excluding hard disk)	6.4W
Operating Temperature	Temperature: 0C--+40C (32F ~ 104F)
Operating Humidity	Humidity: Less than 90%RH"