



## Feature

- 8\*10/100Mbps PoE port; 2\*100/1000Mbps Uplink port;
- 1\*1000Mbps SFP
- 250m Distance;
- Vlan Support
- REALTEK Chipset
- Support IEEE802.3AF/AT
- Whole Power: 120W(52V 2.3A)
- All port supported by MDI/MDIX auto flip and self negotiation
- Supply 8 10/100Mbps adaptive high speed forwarding data packet non-lost port.
- Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.
- Each port max. Power supply reached 30W.

## Specification

Model	HH-SW10 2P8 S1
Product	8+2+1 Port 250m POE Switch (Built-in)
POE Port	1 to 8 support IEEE802.3AF/AT Standard
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	Both 1/2+, 3/6- and 4/5+7/8-
Whole Power	≤120W (52V 2.3A)
POE Protocol	IEEE 802.3af/IEEE 802.3at
POE Type	End-span
Power Distance	≤250m
Network Standard	IEEE 802.3 IEEE802.3u 802.3x 802.3af/at
Network Medium	10/100BASE-TX: 5 class and above non shielded twisted pair
Data Distance	≤250m
Switch Capability	12Gbps
Forwarding Mode	Store and forward
Forwarding Rate	100BASE-T: 148800pps / port 1000BASE-T: 1488000pps / port
MAC Address	MAC address table 2K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	LINK/ACT.100Mbps; POE Status Indicator; Power indicator; Extender
Working Environment	Working temperature: -10-- 55C
Weight	1.2kg
Size	20mm*118mm*44mm (L*W*H)