



Feature

- 16*10/100Mbps POE port; 2*100/1000Mbps Uplink; 1*1000Mbps SFP
- 250m Distance;
- Vlan support
- Support IEEE802.3AF/AT
- nadia@juanvision.com All port supported by MDI/MDIX auto flip and self-negotiation
- Supply 18 10/100/1000Mbps adaptive high speed forwarding data packet non-lost port.
- Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.
- Each port max. Power supply reached 30W.

Specification

Model	HH-SW18 2P16 S1
Product	16+2+1 port 250m POE switch(Built-in)
PoE Port	1 to 16 port support IEEE802.3af/at
UP link port	17 th -18 th port support 1000Mbps
PoE output	15.4W/30W IEEE802.3af/at
PoE whole power	≤250W
PoE type	End-span
Power distance	≤250m
Network Standard	IEEE 802.3 IEEE802.3u 802.3x 802.3af/at
Network Medium	10/100BASE-TX: 5 class and above non shielded twisted pair
Data Distance	≤250m
Switch capability	12Gbps
Forwarding Mode	Store and forward
Forwarding Rate	10BASE-T: 14880pps/port 100BASE-tx: 148800pps/port 1000BASE-T: 1488000pps/port
MAC Address	2K MAC address table
Port function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
Indicator	LINK/ACT. 100Mbps; POE Status indicator; POWER indicator; EXTENDER indicator
Working Environment	Working Temperature: -10-- 55C
Input power	AC100-240V 50/60HZ
Weight	2.1kg
Size	270mm*180mm*44mm (L*W*H)