



Feature

- 4*10/100Mbps POE port, 2*10/100Mbps UP Link port
- 250m Distance
- Support IEEE802.3AF/AT
- Whole Power: 78W (52V 1.5A)
- All port supported by MDI/MDIX auto flip and self negotiation
- Supply 4 10/100Mbps adaptive high speed forwarding data packet non-lost port.
- Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.
- Each port max. Power supply reached 30W.

Specification

Model	HH-SW6 2P4
POE Port	1 to 4 support IEEE802.3AF/AT Standard
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	Both 1/2+, 3/6- and 4/5+7/8-
Whole Power	≤ 78W (52V 1.5A)
POE Protocol	IEEE 802.3af/IEEE 802.3at
POE Type	End-span
Power Distance	≤ 250m
Network Standard	IEEE 802.3, IEEE802.3u, 802.3x, 802.3af/at
Network Medium	10/100BASE-TX: 5 class and above non shielded twisted pair
Data Distance	≤ 250m
Switch Capability	1.6Gbps
Forwarding Mode	Store and forward
Forwarding Rate	10BASE-T: 14880PPS/port 100BASE-tx: 14800pps/port
MAC Address	MAC address table 1K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	LINK/ACT.100Mbps; POE Status Indicator; Power indicator; Extender
Working Environment	Working temperature: -10-- 55°C
Weight	1kg
Size	200mm*118mm*44mm (L*W*H)