



# DVR 5IN1 SYSTEM

AHD /TVI /CVI /CVBS /IPC SYSTEM SUPPORT

# H.265

# 5MPiXEL

Video Recorder



## DVR 7500 SERIES



# DVR 5IN1 SYSTEM

AHD /TVI /CVI /CVBS /IPC SYSTEM SUPPORT

## Specification

**5MPiXEL HD**  
Video Recorder



## Feature

- \* Analog video-input 16CH inputs
- \* IP Video Input 4ch, (only IP up to 20ch)
- \* Composite Video Input up to 20ch (Analog video + IP video)
- \* Compression Audio: G.711a / Video: H.264 / H.265
- \* Playback 5MPiLite: 96fps (Max 8CH playback)  
4MPiLite: 128fps (Max 8CH playback)  
1080P: 120fps (Max 8CH playback)  
720P: 240fps (Max 8CH playback)
- \* Ethernet 1 RJ45 100/1000Base-T
- \* USB2.0\*1(front) / USB3.0\*1+(rear)
- \* Audio 4 in / 1 out
- \* HDD1 SATA HDD, up to 8TB
- \* RS485 1
- \* Input Voltage/Current 1HDD: DC12V/2A

# H.265

## DVR 7500 SERIES

Model	HA-75516P-V1
Inputs	16Mbps ~ 80Mbps IP Bandwidth default is 16Mbps, decrease one Analog channel can increase 4Mbps default decoding performance 1080P 120 fps decrease one Analog channel can increase 1080P 8fps
Out	96Mbps
Analog video-input	16CH inputs
Live	
IP Video Input	4ch, (only IP up to 20ch)
Composite Video Input	up to 20ch (Analog video + IP video)
Performance	
Installation wizard	Yes
Recording and Playback	
Compression	Audio: G.711a / Video: H.264 / H.265
Display resolution	Analog: 5MP-Lite: 20fps / 4MP-Lite: 30 fps 1080P / 720P / 960H: 30fps / IP: 4MP / 1080P / 720P Single IP channel preview up to 2MP 30 fps multi-channel preview only substream
Speed	Analog: 5MP-Lite: 12fps (each ch) 4MP-Lite: 16fps (each ch) / 3MP-Lite: 19fps (each ch) 1080P: 15fps (each ch) 720P: PAL: 25fps (each ch) / NTSC: 30fps(each ch) IP: PAL: 25fps (each ch) / NTSC: 30fps(each ch) Sub-stream Max PAL: 704*576:10fps(each ch) NTSC: 704*480:10fps (each ch)
Event	MD (Sensitivity Level 1-8) Video loss Beep, Email, Push notification to Mobile APP
Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x,1/16x)
Playback	5MPiLite:96fps (Max 8CH playback) 4MPiLite: 128fps (Max 8CH playback) 1080P: 120fps (Max 8CH playback) 720P:240fps (Max 8CH playback)
UI/Monitoring	
Local	UI5.0
WEB	IE10/11
Mobile viewer	Rxcamview
Push N/Atification	TUTK/RS
P/W Reset	Password Reset: Press 3 seconds Factory Reset: Press 8 seconds
Monitors	
BNC	1 (704*576)
VGA	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
HDMI	1 (1024*768,1280*720,1280*1024,1440*900,1920*1080, 2560*1440(2K),3840*2160(4K))
Ethernet	1 RJ45 100/1000Base-T
USB	USB2.0*1(front) / USB3.0*1+(rear)
Audio	4 in / 1 out
E-sata	0
HDD	1 SATA HDD, up to 8TB
RS485	1
Alarm Input / out	0
General	
OSD Language	More
Dimension (WxDxH)	300X227X53mm
Input Voltage / Current	1HDD: DC12V/2A
Power consumption (excluding hard disk)	13.8W
Operating Temperature	Temperature: 0C ~+ 40C (32F ~ 104F)
Operating Humidity	Humidity: Less than 90%RH