



Feature

- * Using CAT.5 network patch cords support power for the wireless AP and IP camera
- * Networking standard: IEEE802.3af/at/bt
- * POE power light blinks to determine the power status of the receiving end, and each blink is 2.7 watts.
- * PoE Watchdog AI Function: Detection front-end PoE cameras and PD, Automatic detection, Automatic restart
- * Upload port automatic flip (Auto MDI / MDIX)
- * Network performance: Store-and-forward
- * Intelligent power distribution and secure power supply system
- * The port power is 60 watts, it is convenient for high-power device
- * Zero configuration feature power supply is automatically supplied to the adaptive equipment
- * Professional thunder design, Overtemperature protection , short circuit protection ,high reliability, high stability
- * Nature cooling, small, compact, mute, all the designs are convenient for you to put
- * Support: port no-load saving power

Specification

Model	HG-SW8 8P8G
Network Interface	PoE (1~8) UP-LINK (PoE1~ 8)
Transmission Rate	2000Mbps Full Duplex; 10 or 100 or 1000Mbps Half Duplex Network Interface: 10BASE-T or 1000BASE-TX RJ45 port of Ethernet
Performance & Specification	Bandwidth: 16.0Gbps Network Latency (10 to 1000Mbps): ≤16μs (use the 64byte package size) MAC address table: 8K The Frame Filter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port, 1488000pps the most for 1000M port
Networking Standard	IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX/IEEE802.3ab 1000Base-T IEEE 802.3xFlowControl IEEE 802.3af/at/bt Power over Ethernet
PoE Core Of Power Cable	Default: 1/2(+), 3/6(-); 1245(+),3678(-);
PWR Light	PWR Light no extinguish
Power Support	Power input: DC 5~52V 60W, Power output: PoE1~4Port:1/2(+52V),3/6(GND) PoE 7~8 Port:1245(+53V),3678(GND) compatible1/2(+52V),3/6(GND)
Physical Specifications	Size(L*W*H) 187mm*139mm*43mm
Working Environment	Operating Temperature: -10°C ~55°C (-14°~131°F) Storage Temperature: -40°C ~70°C (-104°~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
Electromagnetic Compatibility	CE mark FCCPart15, Class B VCCI ClassBEN55022 (CISPR 22) C-Tick
Package Content	AC Power Cable , Installation Manua