



HU-AL01(L)

HU-AL01(R)

Specification

Model	HU-AL01
Power supply	4 standard AA Alkaline Battery
Battery life	Over 10000 times normal unlocking (Around 12 months)
Static current	≤ 15 uA
Reading current	≤ 20mA
Unlock current	300mA
Storage humidity	≤ 95%RH
Working temperature	-0°C ~+ 70°C
Working humidity	10-90% RH
Card reading distance	0-3cm
Reading time	<0.5s

- Unlocking by ID card + mechanical key in emergency
- Support card type: Card ID 125KHz
- Material: Stainless 201 stainless steel
- Powered by 4pcs AA Alkaline battery
- Battery life: approx 1 year
- Low voltage alarm



ID Card to open door
Add Card Maximum 200 Pcs.



Mechanical keys (2 pcs) to open door
Emergency Key open the door



Deadbolt + Anti-card Latch
(ANSI Mortise)
Standard 5-bolt electronic cylinder



Handle
Safe and modern handle design stainless steel



Back Bolt Knob
There is a Bolt knob on the back of the lock, deadbolt latch out to improve your security



4X AA Batteries
4 section 6V 5# alkalinity for 10,000 times unlocking. Low voltage warning, when it is low 4.8V

Accessories	อุปกรณ์เสริม
	บัตรประเภทบัตรแบบหนา
	บัตรประเภทบัตรแบบบาง
	บัตรประเภทบัตรทรงหยดน้ำ