

HV-P1820



คุณสมบัติหลัก

- Power supply output 18Ch.
- Power input AC110V~240V
- Pwer output DC12V/20A.
- Support LED indicator status for each output when problem occurs only affect the individual output, other outputs still working;
- Support short circuit protection with PTC fuse (Restoring circuit)
- Support over current protection
- Application for security systems, CCTV, TZ, IR Illuminator, Video processor, Access Control Etc.
- CE, FCC, RoHS

รายละเอียดสินค้า

Input Voltage	AC 100~240V, 50-60Hz
Input Frequency Range	50Hz/60Hz
Output Voltage	DC11.8V-15.9V
Output Voltage Adjustment	Support
Total Output Current	20A.
Total Output Channel	18CH
Output Power	240 Watt.
Fuse Type	"Polymer PTC Resetable fuse (JK60 200) (Max. voltage 60Vdc, Max. 2 ampere) สามารถต้านทานทางได้สูงสุด 60 โวลต์, กระแส 2แอมป์"
Fuse Rating	2A
Ripple & Noise	<=150mv
Efficiency	>=80%
Operating Temperature	.-20°C+60°C, 20%~90%RH
Storage Temperature	.-40°C~+85°C, 10%~95%RH
Product Net Weight	2.96kg
Product Dimension	266.5x259x77.6mm.
Material	Metal
Package Dimension	266x86x275mm.