



**CAMERA 9700 SERIES**  
5Megapixel Network Camera

# IP CAMERA

## 5MP Bullet Camera



- |       |           |     |     |       |     |     |                  |     |      |     |          |
|-------|-----------|-----|-----|-------|-----|-----|------------------|-----|------|-----|----------|
|       |           |     |     |       |     |     |                  |     |      |     |          |
| H.265 | Day&Night | WDR | AWB | Defog | HLC | BLC | Motion Detection | PoE | IP67 | VCA | -30°~60° |

# H.265

Compression Code

# 5MP

Network Camera Series





# CAMERA 9700 SERIES

## 5Megapixel Network Camera

# IP CAMERA

## 5MP Bullet Camera



### Feature

- \* H.265+ / H.265 / H.264+ / H.264 / MJPEG coding
- \* Max. resolution: 2592x1944
- \* ICR auto switch, true day / night vision
- \* 30 ~ 50m IR night view distance
- \* 3D DNR, true WDR, HLC, BLC, Defog, NIR, Smart IR and ROI coding
- \* Support image distortion correction
- \* 1CH audio input
- \* Built-in micro SD card slot, up to 256GB
- \* DC12V/PoE power supply
- \* IP 67 ingress protection
- \* Support three streams
- \* Support remote monitoring by smart phones & tablet PCs with iOS and Android OS
- \* Intelligent analytics

# H.265

## Compression Code



### Specification

Model	HP-97B50VPE-E3-AI
Image Sensor	1 / 2.7 °CMOS
Image Size	2592x1944
Electronic Shutter	1/3 s ~ 1 / 100000 s
Iris Type	DC Iris
Min. Illumination	0.02 lux@F1.6, AGC ON; 0 lux with IR; 0.01lux@F1.4, AGC ON, 0 lux with IR
Lens	2.8-12mm@F1.4, H.FoV: 92.6-28.9; V.Fov: 67.5-21.7; D.FoV: 121.0-36.1
Focus	Motorized
Lens Mount	Φ14
Day & Night	ICR
Wide Dynamic Range	120dB
BLC / HLC / Defog	Yes
S/N Ratio	50dB
Digital NR	3D DNR
Angle Adjustment	Pan: 0-360° ; Tilt: 0-90° / Rotation: 0-360°
Image	
Video Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	5MP(2592x1944 ), 4MP(2592x1520), 2K(2560x1440), 3MP(2304x1296), 1080P(1920x1080), 720P(1280x720), D1, CIF, 480x240
Main Stream	5MP/4MP/2K/3MP/1080P/720P (60Hz: 1~ 30fps; 50Hz: 1~25fps) HFR mode: 1080P/720P (60Hz: 1~ 60fps; 50Hz: 1~50fps)
Sub Stream	720P/D1/CIF/480x240 (60Hz: 1~30fps; 50Hz:1~25fps)
Third Stream	D1/CIF/480x240 (60Hz: 1~30fps; 50Hz: 1~25fps)
Bit Rate	64 Kbps ~ 8 Mbps
Bit Rate Type	VBR / CBR
Audio Compression	G711A / U
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ 45 10M/100M self-adaptive Ethernet port
Audio	1CH audio input
Storage Built-in	micro SD card slot; up to 256GB
Reset	Yes
Intelligent Analytics (Smart Events)	
Perimeter Protection	Line crossing, region entrance/exiting/intrusion (human/motor vehicle/ non-motor vehicle classification)
Statistics	Target counting by line/area, heat map
Exception Detection	Scene change, video blur and abnormal color detection
Face Detection	Face detection and face capture
Other Events	Abandoned/missing object detection
Video Metadata	Simultaneously captures human body, motor vehicle and non-motor vehicle and extracts 13 human features, 5 motor vehicle features and 1 non-motor vehicle feature
Functions	
Remote Monitoring	Web Browser/TVT NVMS2.0/NVR/mobile APP
Web Browser	IE11(plugin-in required)/Chrome 89.0+/Edge 89.0+/Firefox 87.0+/Safari 14.0+
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTMP, RTCP, PPPoE, DDNS, SMTP, FTP, SNMP,HTTP, 802.1x, UPnP, HTTPS, HTTP POST, QoS
Interface Protocol	ONVIF
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection, SD card error, SD card full
General Function	Watermark, video mask, heartbeat, image distortion correction, corridor pattern
Security	Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP/HTTPS
PoE	Yes , IEEE802.3af
IR Distance	30 ~50 m
Ingress Protection	IP67
Others	
Power Supply	DC12V/PoE
Power Consumption	< 8.5W < 9W
Storage Conditions	-30C-65C (-22F-149F), Humidity: less than 95 % (non-condensing)
Operating Conditions	-30C-60C (-22F-140F), Humidity: less than 95 % (non-condensing)
Dimensions (mm)	217.8x80.5x80.3