

Specification



PoE Watchdog



Bt port support 60W



Hybrid PoE



Industrial grade chip



6KV Lightning protection



8KV ESD protection



Multiple installation



Temperature

Model	HS-SW10 2P8 BT-AI
Ports	PoE Ports: PoE1~8 100Mbps 60W PoE Ports: PoE7~8 100Mbps Uplink Ports: LAN1~2 100Mbps
Transmission Rate	200Mbps Full Duplex; 10 or 100Mbps Half Duplex
Transmission Distance	130m
Performance	Bandwidth: 2.0Gbps Network Latency (10 to 100Mbps): <16μs (use the 64byte package size) MAC address table: 2K The Frame Filter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port
Networking	IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3xFlowControl IEEE 802.3af/at/bt Power over Ethernet
Power Support	Power input: AC 180V~240V Totals ≤ 120W
Power output	PoE1~6Port: 1/2(+52V), 3/6(GND) ≤ 30W PoE7~8Port: 1245(+53V), 3678(GND) compatible 1/2(+52V), 3/6(GND) ≤ 60W
Size(L*W*H)	187mm*139mm*43mm
Working	Operating Temperature: -30 ~60 Storage Temperature: -40 ~70 Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing