

Specification



PoE Watchdog



Bt port support 60W



Hybrid PoE



Industrial grade chip



6KV Lightning protection



8KV ESD protection



Multiple installation



Temperature

Model	HS-SW10 2P8 S1 HBT-AI
Ports	<p>PoE Ports: PoE1~6 100Mbps</p> <p>PoE Ports: PoE7~8 1000Mbps</p> <p>60W PoE Ports: PoE7~8 1000Mbps</p> <p>Uplink Ports: LAN1~2 1000Mbps</p> <p>SFP Ports: SFP1 1000Mbps</p>
Transmission Rate	<p>2000Mbps Full Duplex;</p> <p>10 or 100 or 1000Mbps Half Duplex</p>
Transmission Distance	130m
Performance	<p>Bandwidth: 11.2Gbps</p> <p>Network Latency (10 to 1000Mbps):</p> <p>< 16μs (use the 64byte package size)</p> <p>MAC address table:8K</p> <p>The Frame Filter & Transmission Rate:</p> <p>14800pps the most for 10M port,</p> <p>148800pps the most for 100M port,</p> <p>1488000pps the most for 1000M port</p>
Networking	<p>IEEE 802.3i 10BASE-T</p> <p>IEEE 802.3u 100BASE-TX</p> <p>IEEE 802.3xFlowControl</p> <p>IEEE 802.3ab 1000BASE-T</p> <p>IEEE 802.3z:1000BASE-X</p> <p>IEEE 802.3af/at/bt Power over Ethernet</p>
Power output	<p>PoE1~6Port: 1/2(+52V), 3/6(GND)≤30W,</p> <p>PoE7~8Port: 1245(+53V), 3678(GND)</p> <p>compatible1/2(+52V), 3/6(GND)≤60W</p>
Size(L*W*H)	187mm*139mm*43mm
Working	<p>Operating Temperature: -30C~60C</p> <p>Storage Temperature: -40C~70C</p>
Operating Humidity	10%~90% non-condensing
Storage Humidity	5%~90% non-condensing