



Feature

- * PoE Ports: PoE1~22 100Mbps
- PoE Ports: PoE23~24 1000Mbps
- 60W PoE Ports: PoE23~24 1000Mbps
- Uplink Ports: LAN1~2/PoE23~24 1000Mbps
- DC Port: 5V1A DC Power output
- * 2000Mbps Full Duplex; 10 or 100 or 1000Mbps Half Duplex
- * Bandwidth: 12.4Gbps
- * Network Latency (10 to 1000Mbps)
- * MAC address table: 8K
- * IEEE 802.3i 10BASE-T / IEEE 802.3u 100BASE-TX
- IEEE 802.3xFlowControl / IEEE 802.3ab 1000BASE-T
- IEEE 802.3af/at/bt Power over Ethernet
- * Power input: AC 180V~240V / Total 300W
- * Power output: PoE1~22Port: 1/2 (+52V), 3/6 (GND) 30W
- PoE23~24Port: 1245 (+53V), 3678 (GND)
- compatible 1/2 (+52V), 3/6 (GND) 60W

Specification

Model	HS-SW26 2P24 HBT-AI
Ports	PoE Ports: PoE1~22 100Mbps PoE Ports: PoE23~24 1000Mbps 60W PoE Ports: PoE23~24 1000Mbps Uplink Ports: LAN1~2/PoE23~24 1000Mbps DC Port: 5V1A DC Power output
Transmission Rate	2000Mbps Full Duplex; 10 or 100 or 1000Mbps Half Duplex
Transmission Distance	130m
Performance	Bandwidth: 12.4Gbps Network Latency (10 to 1000Mbps): < 16μs (use the 64byte package size) MAC address table: 8K The Frame Filter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port, 1488000pps the most for 1000M port
Networking	IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3xFlowControl IEEE 802.3ab 1000BASE-T IEEE 802.3af/at/bt Power over Ethernet
Power Support	Power input: AC 180V~240V / Total 300W Power output: PoE1~22Port: 1/2 (+52V), 3/6 (GND) 30W PoE23~24Port: 1245 (+53V), 3678 (GND) compatible 1/2 (+52V), 3/6 (GND) 60W
Size (L*W*H)	430mm*180mm*45mm
Working	Operating Temperature: -30°C ~ 60°C Storage Temperature: -40°C ~ 70°C Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing