



Cloud service ,Multi browser access,Web management

DVR 8500 SERIES

SUPPORT 5IN1 SYSTEM

AHD / TVI / CVI / CVBS / IPC SYSTEM SUPPORT



HAC-85504A

4K-N PIXEL HD

Video Recorder





DVR 8500 SERIES

SUPPORT 5IN1 SYSTEM

AHD / TVI / CVI / CVBS / IPC SYSTEM SUPPORT



Feature

- * Support 4ch 4K-N unreal-time encoding;
- * Support XVI,AHD, TVI,CVI, CVBS, IP video input;
- * support VGA maximum 1080P output, HDMI up to 4K output;
- * Mini 1U Case, 1SATA(Up to 14TB);
- * 1*10/100Mbps auto-sensing Ethernet port, RJ45 port
- * Automatic networking support, a key to add equipment;
- * Support the Onvif protocol;
- * Support GB28181 (Optional);
- * Cloud services, P2P, alarm information push to phone;
- * Support remote access, support ARSP;
- * Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc;
- * Mobile phone remote monitoring (iOS, Android);
- * Multi browser access (IE, Chrome, Firefox, Safari);
- * Support for more than twenty languages;
- * Perfect protection circuit,unique triple watchdog function
- * Support WEB, CMS, VMS, MYEYE Platform;
- * Support coaxial control, coaxial audio
- * Support human detection, face detection Vehicle detection and other intelligence

4K-N PIXEL Video Recorder **HD**

Specification

Model	HAC-85504A
Codec	H.265+/H.265/H.264
Preview	4ch4K-N@12fps(6in1) / 4ch4M@15fps(6in1) 4ch3M@18fps(6in1) / 4ch1080P(6in1) default: 4K-N
Encode	4ch4K-N@12fps(6in1) / 4ch4M@15fps(6in1) 4ch3M@18fps(6in1) / 4ch1080P(6in1) default: 4K-N
Decode	1ch4K-N12fps(6in1) / 1ch4M@15fps(6in1) 1ch3M@18fps(6in1) / 1ch1080P default: 4K-N
Multi-mode	Analog: 4ch 4K-N hybrid: 4*4K-N(analog) +4*5M(network) IP: 16ch 1080P / 16ch 5M
Playback	4/2/1ch
Audio	
Coaxial audio	Support
Compression	G.711a
Intercom	Support
Management	
Record mode	Manual>Alarm>Motion detection>Timing
Inquire mode	Inquire by Time/Calendar/Event/Channel
Storage mode	HDD Storage, Network Storage
Backup	Network, USB, SATA
Interface	
Video input	4*BNC(Support Coaxitron)
HDMI output	1*HDMI (MAX:4K)
VGA output	1*VGA (MAX:1080P)
Audio I/O	1/1
Alarm I/O	0/0
Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
PTZ control	Support for multiple PTZ protocol
USB Port	2*USB 2.0 ports
HDD	1*SATA interface (Up to14TB)
General	
Temperature	0C - + 55C
Humidity	10% -90% RH
Power supply	12V/2A
Consumption	<10W (Without HDD)
Weight Around	1KG
Dimension	255mm(L)* 215mm(W)* 44mm(H)