



# 5000 SERIES

IP CAMERA SUVEILANCE

## HP-55D80STPE



# 8M PIXEL

IP Camera Series





# 5000 SERIES

## IP CAMERA SUVEILANCE



## Feature

- \* Image Sensor 1/3"
- \* Pixels 3840(H)x2160(V)
- \* Min. Illumination Color:0.05Lux @F1.2  
B/W: 0.005 Lux @F1.2
- \* Video Encoding Format H.264/H.265
- \* Stream Dual steam
- \* Auto Electric Iris / Fixed lens 3.6mm.
- \* IR LED IR LED 2 Pcs and white light 2pcs
- \* IR Distance 20-30M. / IR CUTSupport
- \* Day&Night Star IR, full color, Black & white,smart alert
- \* Cloud / ONVIF Support
- \* Power DC12V / Ø5.5\*2.1mm
- \* RJ45 x1 (100 Mbps)
- \* Audio IN Built-in microphone

## Specification

Model	HP-55D80STPE
Image Sensor	1/3"
Pixels	3840(H) x 2160(V)
Min. Illumination	Color: 0.05Lux @F1.2 / B/W: 0.005 Lux @F1.2
Shutter Speed	1/50(1/60)-1/10,000s
Video Encoding Format	H.264/H.265
Video Coding Rate	32 Kbps~8Mbps
Audio Format	G.711A
Stream	Dual steam
Main Stream	Main Stream 8MP 3840*2160@15fps; 5MP 2592*1944@25fps
Sub Stream	Sub stream D1@15fps
Bitrate control	CBR/VBR
Signal System	PAL/NTSC
<b>Lens</b>	
Mount Type	Ø12
Auto Iris	Auto Electric Iris
Focal Length	Fixed lens 3.6mm.
Focus Mode	Manual focus
Angle of View	82°
<b>Infrared</b>	
IR LED	IR LED 2 Pcs and white light 2pcs
IR Distance	20-30M.
IR CUT	Support IR CUT
Day&Night	Star IR, full color, Black & white, smart alert
<b>Network</b>	
Protocol	TCP/IPv4, HTTP, DHCP, FTP,RTSP
Browsers	IE
Cloud	Support (APP:Linklemo)
ONVIF	Support
Network Upgrade	Support
User Management	Support
Auto Maintain	Support
Import&Export Config	Support
<b>Electrical</b>	
Power	DC12V / Ø 5.5*2.1mm
Power Consumption	<8W Max.
POE	Support
<b>Environmental</b>	
Storage Temperature	-20C~+60C
Operating Temperature	0C~+40C
Working Humidity	90% RH (Non-Condensing)
<b>Hardware Interface</b>	
RJ45	x1 (100 Mbps)
Audio IN	Built-in microphone
LED Indicator Status	x2
Power Input	DC12V
<b>Machanical</b>	
Case Material	Metal Case
Weight	240g
Dimension	183mm*71mm*60mm

