



KIT SET 4 CH

5 IN 1 DVR Recorder

2MP **PIXEL** **HD**
KIT SET CAMERA



FI-ECO4KIT20

2MP HD DIGITAL VIDEO RECORDER



FIERS 2SEE





FIRES

KIT SET 4 CH 5 IN 1 DVR Recorder



H.265 **H.264** **ONVIF** **HDMI**

Feature

- * 4Mbps ~ 20Mbps IP Bandwidth deful is 4Mbps, decrease one Analog channel can increase 4Mbps (default decoding performance 1080P 60fps)
- * Analog video-input 4CH inputs
- * IP Video Input 1ch,(only IP up to 5ch)
- * Composite Video Input up to 5 ch (Analog video + IP video)
- * Compression Audio: G.711a / Video: H.264/H.265
- * Playback 5MP-lite:80fps / 4MP-lite: 120fps 1080P: 120fps / 720P:120fps
- * Ethernet 1 RJ45 10/100Base-T
- * USB 2.0*2 (front)
- * HDD1 SATA HDD, Up to 10 TB capacity
- * Input Voltage / Current DC12V/2A



FIERS 2SEE



Specification

Model	FI-EC04
Inputs	4Mbps ~20Mbps IP Bandwidth deful is 4Mbps, decrease one Analog channel can increase 4Mbps (default decoding performance 1080P 60fps)
Out	32Mbps
Analog video-input	4CH inputs
Live	
IP Video Input	1ch, (only IP up to 5ch)
Composite Video Input	up to 5 ch (Analog video + IP video)
Performance	
Installation wizard	Yes
Recording and Playback	
Compression	Audio: G.711a / Video: H.264 / H.265
Display resolution	Analog: 5MP-Lite: 20fps / 4MP-Lite: 30fps 1080P / 720P / 960H: 30fps IP: 1080P / 720P Single IP channel preview up to 2MP 30 fps multi-channel preview only substream
Speed	Analog: 5MP-Lite:20fps (each ch) 4MP-Lite: 30fps (each ch) 1080P / 720P: PAL: 25fps (each ch) NTSC: 30fps (each ch) IP: PAL: 25fps (each ch) / NTSC: 30fps (each ch) Sub-stream PAL: 704*576: 10fps (each ch) NTSC: 704*480: 10fps (each ch)
Event	MD (Sensitivity Level 1~8) / Videlo loss Email, Push notification to Mobile APP
Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x, 1/16x)
Playback	5MP-lite: 80fps / 4MP-lite: 120fps 1080P: 120fps / 720P: 120fps
UI / Monitoring	
Local	UI5.0
WEB	N/A
Mobile viewer	Fires2see
Push N/Atification	yes
P/W Reset	
Factory Reset	Press 10 seconds
HDMI	1(1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 ,EDID)
Ethernet	1 RJ45 10/100 Base-T
USB	USB 2.0*2 (front)
HDD	1 SATA HDD, Up to 10 TB capacity
General	
OSD Language	English/French/Spanish/Portuguese/German/Italian/Greek/Danish Finnish/Russia/Hebrew/Turkish/Bulgarian/Arabic/Korean/Japanese Thai/Hindi/Romanian/Dutch/Polish
Dimension (WxDxH)	230*215*47mm
Input Voltage / Current	DC12V/2A
Power consumption (excloding hard disk)	3.6W
Operating Temperature / Humidity	Temperature: -10C ~+ 50C (14F ~ 122F) Humidity: Less than 90%RH"



FIRES

KIT SET 4 CH 5 IN 1 DVR Recorder



H.265 **H.264** **ONVIF** **HDMI**

Feature

2MP **PIXEL** **HD**
KIT SET CAMERA

- * 1/3" Progressive CMOS
- * Resolution 2MP 1920(H) x 1080(V)
- * AHD/TVI/CVI: P/@25fps N/@30fps CVBS: 960H
- * Focal Length (Zoom Ratio) 3.6MM
- * Lens Type Fixed lens
- * IR Distance 20M
- * Remote control interface ACP (AHD Coax Protocol)
- * Ingress Protection IP66
- * Input Voltage / Current 12V DC



FIERS 2SEE

Available on the iPhone
App Store

ANDROID APP ON
Google play

Specification

Model	FI-ECOB20
Imaging Device	SC2336 1/3" Progressive CMOS
Scanning System	progressive scanning
Video Output	BNC
Resolution	2MP 1920(H) x 1080(V)
Max. Framerate	AHD / TVI / CVI: P / @25fps N / @30fps CVBS: 960H
Focal Length (Zoom Ratio)	3.6MM
Max. Aperture Ratio	F2.0
Angular Field of View	H:74.26 / V:41.02 / D:87.4
Min. Object Distance	0.2m
Lens Type	Fixed lens
Operational	
Audio	Audio over coaxial
Audio Range	7M
IR Distance	20M
On Screen Display	English
Day & Night	Ext / Color / B/W
Backlight Compensation	Off / User BLC
Wide Dynamic Range	D-WDR (Off/On)
Digital Noise Reduction	2D DNR
Gain Control	Auto
White Balance	ATW
Electronic Shutter Speed	Auto
Reverse	Mirror
Remote control interface	ACP (AHD Coax Protocol)
Environmental	
Operating Temperature	-30C ~ 55C / 90%
Operating Humidity	-30C ~ 55C / 90%
Ingress Protection	IP66
Electrical	
Input Voltage / Current	12V DC
Power Consumption	IR OFF ≤0.5W IR ON ≤3.5W
Mechanical	
Color / Material	Plastic
Dimension (WxHxD)	TBD
Weight	TBD