



KIT SET 4 CH 5 IN 1 NVR Recorder

4M PIXEL 
KIT SET CAMERA



FI-TOP4KIT40

4MP NETWORK VIDEO RECORDER



FIERS 2SEE





FIRES

KIT SET 4 CH 5 IN 1 NVR Recorder



H.265 **H.264** **ONVIF** **HDMI**

Feature

- * Resolution 8MP, 5MP, 3MP, 2MP (1080P) 1.3MP (960P), 1.0MP (720P)
- * Compression Audio: G.711A,G / 711U Video: H.264 / H.264+ / H.265 / H.265+
- * Frame rate 4K: 30fps / 4MP: 60fps / 2MP: 120fps
- * PlaybackMax 4CH playback
- * Mobile viewer Fires2see
- * PoE 4*RJ45, 802.3at/af
- * Ethernet 1 RJ45 10/100 Base-T
- * Audio out 1
- * HDD1 SATA HDD, up to 10TB
- * Input Voltage / Current DC48V/1.2A



FIERS 2SEE



Specification

Model	FI-TOP4
Resolution	8MP, 5MP, 3MP, 2MP (1080P), 1.3MP (960P) 1.0MP (720P)
Inputs	50Mbps
Out	48Mbps
Live / Playback	
Compression	Audio: G.711A, G/711U Video: H.264 / H.264+ / H.265 / H.265+
Frame rate	4K: 30fps / 4MP: 60fps / 2MP: 120fps"
AI	yes
Event	MD (Sensitivity Level 1~8) / Videlo loss Beep, Email, Push notification to Mobile APP
Playback function	Fast forward / backward (2x, 4x, 8x, 16x) Slow forward (1/2x, 1/4x, 1/8x, 1/16x)
Playback	Max 4CH playback
Fisheye	Use WEB CMS, device does not support
UI/Monitoring	
Local	UI5.0
WEB	IE10/11 / Safari V12.1 above Firefox V.52 above / Google chrome V.57 above Edge V.79 above
Mobile viewer	Fires2see
Push Notification	yes
Interface	
P/W Reset	Factory Reset: Press 10 seconds
VGA	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
HDMI	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, 2560*1440, 3840*2160/EDID)
POE	4*RJ45, 802.3at/af
Ethernet	1 RJ45 10/100 Base-T
USB	USB 2.0*1 (front) / USB 2.0*1 (rear)
Audio out	1
HDD	1 SATA HDD, up to 10TB
General	
OSD Language	English/French/Spanish/Portuguese/German/Italian Greek/Danish/Finnish/Russia/Hebrew/Turkish Bulgarian/Arabic/Korean/Japanese/Thai/Hindi Romanian/Dutch/Polish
Dimension (WxDxH)	300X227X53mm
Input Voltage / Current	DC48V/1.2A
Power consumption (excluding hard disk)	5W
Operating Temperature / Humidity	Temperature: -10C--+50C (14F-122F) Humidity: Less than 90%RH



FIRES

KIT SET 4 CH 5 IN 1 NVR Recorder



ONVIF

HDMI

Feature

4M PIXEL HD
KIT SET CAMERA

- * 1/3" Progressive CMOS / H.265/H.264
- * Resolution 4MP 2560(H) x 1440(V)
- * Color 0.002 Lux@ (F1.0,AGC ON); B/W 0 lux@IR ON
- * Focal Length 3.6 mm
- * IR LED1 / Warm Light2
- * Red Blue Light 2 (1 Red & 1 Blue)
- * On-Board Storage Micro SD slot, up to 256GB
- * Built-in microphone & Speaker
- * RJ45 (10/100BASE-T)
- * ONVIF Support / IPv4
- * Ingress Protection IP66
- * Input Voltage / Current D12V / POE (IEEE802.3af)



FIERS 2SEE

Available on the iPhone
App Store

ANDROID APP ON
Google play

Specification

Model	FI-TOPB40
Imaging Device	1/3" Progressive CMOS
Effective Pixels	4MP 2560(H) x 1440(V)
Min. Illumination	Color 0.002 Lux @ (F1.0, AGC ON); B/W 0 lux @ IR ON
Lens Type	
Focal Length (Zoom Ratio)	3.6 mm
Max. Aperture Ratio	F No. 1.0
Angular Field of View	Horizontal: 72°, Vertical: 42°, Diagonal: 90°
Min. Object Distance	2m
Lens Type	Fixed (M12)
Operational	
IR LED	1
WarmLight	2
Red Blue Light	2 (1 Red & 1 Blue)
IR Viewable Length	Up to 25m
WarmLight Viewable Length	Up to 20m
Type of complementary light	Default warm light, switchable infrared light
Motion Detection	Off/On (8 Level)
Wide Dynamic Range	DWDR
Digital Noise Reduction	3D DNR
Image Setting	Full Color Mode/Day&Night Mode/Schedule
White Balance	Auto / Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
On-Board Storage	Micro SD slot, up to 256GB
Alarm	NA
Audio	Built-in microphone & Speaker
Hardware Reset	Yes
Smart Feature	SMD (Human&Vehicle Detection (PD&VD) Perimeter Intrusion Detection (PD) Line Crossing Detection (LCD)
Network	
Ethernet	RJ45 (10/100BASE-T)
Video Compression Format	H.265 / H.264
Resolution	Mainstream@ 25fps 4MP (2560x1440) Substream@ 25fps VGA (640x480)
Video Quality Adjustment	512Kbps ~ 4Mbps
Bitrate control method	CBR/VBR
IP	IPv4
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP,SMTP, NTP, HTTPS
Security	complicated password;Authenticated username and password
Application Programming Interface	ONVIF
Web Viewer	IE10/11
Environmental	
Operating Conditions	-35~+60C / less than ≤ 95% RH
Ingress Protection	IP66
Electrical	
Input Voltage / Current	D12V / POE (IEEE802.3af)
Power Consumption	1.2-5W
Mechanical	
Material	Metal & Plastics
Dimensions (HxWxD)	152.3*70.1mm
Weight	282g