

HP-97B502PE-M

5MPIXEL
Network Camera Series



9700 SERIES

5Megapixel Network Camera

H.265



9700 SERIES

5Megapixel Network Camera



Feature

- * H.265+ / H.265 / H.264+ / H.264 / MJPEG coding
- * Max.resolution: 5MP (2880x1620)
- * ICR auto switch, true day / night vision
- * 3D DNR, WDR, HLC, BLC, smart IR, etc.
- * ROI coding
- * 30~50m IR night view distance
- * Built-in micro SD card slot, up to 256GB
- * DC12V / PoE power supply
- * IP 67 ingress protection
- * Support three streams
- * Support remote monitoring by smart phones & tablet PCs with iOS and Android OS
- * Intelligent analytics



Specification

1/2

Model	HP-97B502PE-M
Image Sensor	1 / 2.7 "CMOS
Image Size	2880 x 1620
Electronic Shutter	1 / 1s ~ 1 / 100000s
Iris Type	Fixed Iris
Min. Illumination	0.007 lux @F1.6, AGC ON; 0 lux with IR
Lens	2.8mm@F1.6, H.FoV: 110.5; V.FoV: 57; D.FoV: 13f
Focus	Fixed
Lens Mount	M12
Day&Night	ICR
Wide Dynamic Range	120dB
BLC / HLC / Digital NR	Yes
Defog	No
Angle Adjustment	Pan: 0-360; Tilt: 0-90; Rotation: 0-360
Image	
Video Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub / third stream: H.265+ / H.265 / H.264+ H.264 / MJPEG
H.265 Compression	Main Profile@Level4.1 High Tier
Resolution	5MP (2880x1620), 4MP (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 720P (1280x720), D1, 480x240, CIF
Main Stream	60Hz: 5MP(1~20fps)/4MP/3MP/1080P/720P(1~30fps); 50Hz: 5MP(1~20fps)/4MP/3MP/1080P/720P(1~25fps)
Sub Stream	60Hz: 720P/D1/CIF (1~30fps); 50Hz: 720P/D1/CIF (1~25fps)
Third Stream	60Hz: D1/480x240/CIF (1~30fps); 50Hz: D1/480x240/CIF (1~25fps)
Bit Rate	64 Kbps ~ 8 Mbps
Bit Rate Type	VBR / CBR
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ45
Video Output	No

H.265

9700 SERIES

5Megapixel Network Camera



Feature

- * H.265+ / H.265 / H.264+/ H.264 / MJPEG coding
- * Max.resolution: 5MP (2880x1620)
- * ICR auto switch, true day / night vision
- * 3D DNR, WDR, HLC, BLC, smart IR, etc.
- * ROI coding
- * 30~50m IR night view distance
- * Built-in micro SD card slot, up to 256GB
- * DC12V / PoE power supply
- * IP 67 ingress protection
- * Support three streams
- * Support remote monitoring by smart phones & tablet PCs with iOS and Android OS
- * Intelligent analytics



Specification

2/2

Model	HP-97B502PE-M
Audio	1CH audio input; 1CH built-in MIC
Storage	Built-in micro SD card slot, up to 256GB
Reset	Yes
Functions	
Remote Monitoring	Web browser /TVT NVR/NVMS2.X/Mobile APP
Web Browser	IE (plug-in required)/Google Chrome/Edge/Firefox/Safari
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, RTMP, HTTP, HTTPs, QoS
Interface Protocol	ONVIF
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection, SD card full, SD card error
Smart Event	Video Exception (scene change, video blur and video cast detection), line crossing detection, region intrusion detection, abandoned/missing object detection
General Function	Watermark, IP address filtering, video mask, heartbeat, illegal login lock, corridor pattern
PoE	Yes
IR Distance	30 ~ 50 m
Ingress Protection	IP67
Others	
Power Supply	DC12V/PoE
Power Consumption	< 8.5W
Operating Environment	- 30C ~ 60C (-22F ~ 140F); Humidity: less than 95 % (non-condensing)
Storage Environment	- 30C ~ 65C (-22F ~ 149F), Humidity: less than 95 % (non-condensing)
Dimensions (mm)	217.8 x 80.5 x 80.3
Weight (net)	Approx. 0.66KG
Installation	Ceiling mounting; Wall mounting

H.265