



5M PIXEL
Video Recorder



FACE DETECTION



HA-75508-AI

DVR 5IN1 SYSTEM

AHD / TVI / CVI / CVBS / IPC SYSTEM SUPPORT





5M PIXEL

Video Recorder



FACE DETECTION



Specification

Model		HA-75508-AI
Inputs	16Mbps~48Mbps Decrease one Analog channel can increase 4Mbps Analog channel and digital channel can be converted	
out	64Mbps	
Analog video-input	8CH inputs	
IP Video Input	4ch, (only IP up to 12ch)	
Composite Video Input	up to 12ch (Analog video + IP video)	
Recording and Playback		
Compression	Audio: G.711a, Video: H.264 / H.265	
Display resolution	Analog: 5MP-Lite: 20fps 4MP-Lite: 30 fps 1080P / 720P / 960H: 30fps IP: 5MP / 4MP / 1080P / 720P	
Speed	Main-stream Analog: 5MP-Lite:15fps (each ch) 4MP-Lite: 20fps(each ch) 1080P: 18fps(each ch) 720P: PAL: 25fps(each ch) / NTSC:30fps(each ch) IP: PAL: 25fps(each ch) / NTSC: 30fps(each ch) Sub-stream Max PAL: 704*576: 10fps(each ch) NTSC: 704*480: 10fps(each ch)	
Event	MD (Sensitivity Level 1-8) Videlo loss Beep, Email, Push notification to Mobile APP	
Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x,1/16x)	
Playback	5MP-lite: 90fps (Max 6CH playback) 4MP-lite: 160fps (Max 8CH playback) 1080P: 144fps (Max 8CH playback) 720P: 240fps (Max 8CH playback)	
UI/Monitoring		
Local	UI5.0	
WEB	IE10/11, Safari V12.1 above, Firefox V.52 above Google chrome V.57 above, Edge V.79 above	
Mobile viewer	Rxcamview	
Push N/Atification	yes	

Feature

- * Analog video-input 8CH inputs
- * IP Video Input 4ch, (only IP up to 12ch)
- * Composite Video Input up to 12ch (Analog video + IP video)
- * Compression Audio: G.711a
Video: H.264 / H.265
- * Playback 5MP-lite:90fps (Max 6CH playback)
4MP-lite: 160fps (Max 8CH playback)
1080P: 144fps (Max 8CH playback)
720P:240fps (Max 8CH playback)
- * Audio 8 in /1 out
- * HDD 1 SATA HDD, Up to 10 TB capacity
- * RS485 x1
- * Alarm Input / out 8 in / 1 out
- * Input Voltage/Current DC12V/3A

DVR 5IN1 SYSTEM

AHD / TVI / CVI / CVBS / IPC SYSTEM SUPPORT



5M PIXEL

Video Recorder



Specification



Feature

- * Analog video-input 8CH inputs
- * IP Video Input 4ch, (only IP up to 12ch)
- * Composite Video Input up to 12ch (Analog video + IP video)
- * Compression Audio: G.711a
Video: H.264 / H.265
- * Playback 5MP-lite:90fps (Max 6CH playback)
4MP-lite: 160fps (Max 8CH playback)
1080P: 144fps (Max 8CH playback)
720P:240fps (Max 8CH playback)
- * Audio 8 in /1 out
- * HDD 1 SATA HDD, Up to 10 TB capacity
- * RS485 x1
- * Alarm Input / out 8 in / 1 out
- * Input Voltage/Current DC12V/3A

Model	HA-75508-AI
Intelligent	PID - Perimeter Intrusion Detection (Full channel) LCD - Line Crossing Detection (Full channel) PD&VD - Human&Vehicle Detection (Full channel)
Interface	
P/W Reset	Factory Reset : Press 10 seconds
Monitors	
BNC	1 (704*576)
VGA	1, 1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080
HDMI	1, 1024*768, 1280*720, 1280*1024, 1440*900 1920*1080,2560*1440(2K),3840*2160(4K)
Ethernet	1 RJ45 10/100Base-T
USB	USB2.0*1(front) / USB2.0*1(rear)
Audio	8 in /1 out
HDD	1 SATA HDD, Up to 10 TB capacity
RS485	1
Alarm Input/out	8 in / 1 out
General	
OSD Language	English / French / Spanish / Portuguese German / Italian / Greek / Danish / Finnish Russia / Hebrew / Turkish / Bulgarian / Arabic Korean / Japanese / Thai / Hindi / Romanian Dutch / Polish
Mechanical design	
Dimension (WxDxH)	300*220*53mm
Electrical	
Input Voltage/Current	DC12V/3A
Power consumption	6.4W (excluding hard disk)
Environmental	
Operating Temperature/Humidity	Temperature: -10C ~+ 50C (14F ~ 122F) Humidity: Less than 90%RH"

DVR 5IN1 SYSTEM

AHD / TVI / CVI / CVBS / IPC SYSTEM SUPPORT