



CAMERA 6600 SERIES
2Megapixel Network Camera

2M PIXEL HD
Network Camera Series



HP-66B20PEOD-M

IP CAMERA

2MP Bullet Camera Series





CAMERA 6600 SERIES

2Megapixel Network Camera



Feature

- * Image Sensor 1/3" CMOS
- * Resolution 2.0M (1920x1080)
- * Min. Illumination Color: 0.04Lux@(F2.2,AGC ON)
B/W: 0Lux with IR
- * Video Compression S+265 / H.265 / H.264B / H.264M / H.264H / H.264
- * Focal Length 2.8mm
- * IR LEDs 2 pcs
- * IR Distance 30m
- * Wavelength 850nm
- * Built-In Mic yes
- * System Compatibility onvif Profile S/T
- * Power Supply POE 802.3af; MAX 6W

Specification

Model	HP-66B20PEOD-M
Image Sensor	1/3" CMOS
Min. Illumination	Color: 0.04Lux@(F2.2,AGC ON), B/W: 0Lux with IR
Shutter Time	1s to 1/100,000s
Day & Night	IR-cut filter with auto switch (ICR)
WDR	DWDR
S/N	>37dB
Angle Adjustment	0-360; 0-80; 0-360
Lens	
Lens Type	Fixed
Focal Length	2.8mm
Lens Mount	M12
Aperture Range	F2.2, Fixed
Field of View	100(H); 53(V); 114(D)
DORI Distance	Detect:40.0m, Observe:15.9m Recognize:8.0m, Identify:4.0m
Illuminator	
IR LEDs	2
IR Distance	30m
Wavelength	850nm
Compression Standard	
Video Compression	S+265 / H.265 / H.264B / H.264M / H.264H / H.264
Video Bit Rate	32k-4Mbps
Audio Compression	G.711A / G.711U
Audio Sampling Rate	8kHz
Image	
Max. Resolution	1920x1080@30fps
Main Stream	PAL: 25fps(1920x1080,1280x720,704x576,640x480) NTSC: 30fps(1920x1080,1280x720,704x480,640x480)
Sub Stream	PAL: 25fps(704x576,704x288,352x288,640x360) NTSC: 30fps(704x480,704x240,352x240,640x360)
BLC/HLC/AGC/3D DNR	Yes
White Balance	Auto / Semi-auto / Manual
OSD	1region;16*16 / 32*32 / 48*48
Privacy Mask	4 regions
Defog	Yes
Feature	
Alarm Trigger	Motion Detection
Network	
ANR	ANR
Protocols	HTTP;TCP/IP;UDP;ICMP;DHCP;DNS;NTP;IPv4;RTSP;Telnet;Unicast
System Compatibility	onvif Profile S/T
Remote Connection	1
Mobile Client	N/A
Web	IE10+; Firefox52+; Edge89+; Safari11+; Chrome57+
Interface	
Communication Interface	1 RJ45 10M/ 100M self adaptive Ethernet port
Built-In Mic	Yes
General	
Web Client Language	English
Operating Temperature	-30C -60C
Operating Humidity	0-95%
Storage Temperature	-30C -60C
Storage Humidity	0-95%(non-condensing)
Power Supply	POE 802.3af; MAX 6W
Protection	Surge protection 2000V; Lightning proof 6000V; IP67
Net Weight	0.22kg

