



HP-6608PE

NVR 6600 SERIES

6MP Network Video Record





NVR 6600 SERIES

Network Video Record

Specification



Feature

- * Up to 8-ch IP camera inputs
- * Access / forwarding bandwidth at 60Mbps / 40Mbps
- * S+265, H.265, S+264, H.264 video formats
- * 6MP (30fps)x1, 5MP (30fps)x1, 4MP (30fps)x2, 3MP (30fps)x2, 1080P (30fps)x4 preview decoding capacity
- * 4-ch synchronous playback
- * 6MP (30fps)x1, 5MP (30fps)x1, 4MP (30fps)x1, 3MP (30fps)x2, 1080P (30fps)x3 playback decoding capacity
- * Up to 6TB capacity for each HDD
- * 1xHDMI output
- * HDMI output at up to 4K resolution
- * 1xRJ-45, 10/100 Mbps self-adaptive Ethernet port
- * PoE Interface, 8xRJ45, 10/100 Mbps self-adaptive Ethernet port
- * S+ 265 compression effectively reduces the storage space by up to 75%
- * Support cloud upgrade

Model	HP-6608PE
Access Channel	8
Incoming Bandwidth	60Mbps
Outgoing Bandwidth	40Mbps
Resolution	6MP / 5MP / 4MP / 3MP / 1080P / UXGA / 720P / VGA / 4CIF DCIF / 2CIF / CIF / QCIF
Preview Decoding Capability	6MP(30fps)x1, 5MP(30fps)x1, 4MP(30fps)x2, 3MP(30fps)x2, 1080P(30fps)x4, 720P(30fps)x8, 4CIF(30fps)x8
Third-party Camera Access	ONVIF; RTSP
HDMI Output	HDMI: 1024x768 (60Hz), (720P) 1280x720 (50Hz/60Hz), 1280x800 (60Hz) 1440x900 (60Hz), (1080P) 1920x1080 (50Hz/60Hz), (4K) 3840x2160 (30Hz)
Multi-screen Display	1/3/4/5/6/7/8/9
Compression	
Video	S+265; H.265; S+264; H.264
Audio	G711A; G711U; ADPCM_DIV4
Stream Type	Video; Video & Audio
Network	
Network Protocol	ARP; DDNS; DHCP; DNS; Easy DDNS; HTTP; ICMP; IGMP; IPv4; IPv6; NTP; RTCP; RTP; RTSP; SSH; TCP/IP; UDP; UPnP
Mobile Phone Access	Android; iOS; P2P_A
System Compatibility	CGI; SDK
Web	IE10+; Firefox52+; Edge89+; Safari11+; Chrome57+
Record Playback	
Multi-channel Playback	4
Record Mode	Alarm recording; Schedule recording
Storage Method	Local HDD
Backup	USB storage device
Playback Function	Play / Pause / Stop / Slow / Speed / Backwards 30s / Forwards 30s Full screen / backup (video Editing)
Alarm	
General Alarm	Motion; Mask Alarm; Video Loss
Exceptions Alarm	IP Conflict; MAC Conflict; Network Disconnected; No disk; Illegal Access; Disk Full; Disk R/W error; Video Abnormal; Abnormal found in smart of disk; Abnormal temperature of the disk; PoE overloaded; IPC voltage abnormal; RTC failure
Intelligent Analytics	
AI by Camera	Advanced Intelligence
Storage	
HDD Capacity	Up to 6TB capacity for each HDD
External Port	
USB	2xUSB2.0
HDMI	1xHDMI
Network Interface	1xRJ-45, 10/100 Mbps self-adaptive Ethernet port
SATA	1xSATA interface
PoE	
PoE Interface	8xRJ45, 10/100 Mbps self-adaptive Ethernet port
PoE Budget	45W
Power per PoE Port	30W
Standard	IEEE 802.3 af/at
General	
UI Language	English; Spanish; Italian; Turkish; French; Polish; Dutch; Hebrew; German; Portuguese
Power Supply	DC48V 1.35A
Power Consumption	<10W (without HDD&without PoE)
NetWeight	0.45kg
Operating Temperature	-10C ~ + 55C
Operating Humidity	10%-90%RH
Storage Temperature	-10C ~ + 55C
Storage Humidity	10%-90%RH

