

Specification



Function

- * One-click alarm/help
- * Support 4G networking (optional)
- * HD video intercom
- * Full-duplex voice communication
- * Hierarchical function of authority. If the first level does not answer the call, the next level is automatically transferred
- * Alarm point electronic map display
- * Support multiple response seats
- * Highly sensitive microphone
- * High sound quality loudspeakers
- * Aluminum alloy brushed panel, strong and durable
- * IP network architecture, cross-network segment, cross-routing
- * Video linkage multi-screen (optional)
- * Monitoring and listening function
- * Recording and video function (stored locally in the server, exportable)
- * Broadcast voice function
- * Remote control of APP visual intercom (optional)

Model	HV-18PDCZ
Processor	High performance embedded SOC processor
Operating System	Embedded LINUX operating system
Sensor CMOS	sensor with 200W pixels
Video compression	H.264/30FPS
Audio input built-in	highly sensitive omnidirectional microphone
Audio output	built-in speaker + 1×LINE OUT
Compression standards	G.711, G.713, GSM, DAC
Compression bit rate	64KBPS/8KBPS
Sound quality	Professional echo cancellation and noise suppression
Ethernet	10M/100M adaptive
Network protocols	TCP/IP and DNP
Network port	10/100M Adaptive Ethernet port
Alarm	interface 3 x switching quantity input, 1 x switching quantity output
Power supply	DC 12V 1A
Power consumption	≤5W
Aluminum	alloy wire drawing panel
Dimensions	206mm×120mm×38mm
Installation dimensions	201mm x 114mm x 32mm
Operating temperature	-30°C to 70°C