



# DVR 4000 SERIES

5.0MPixel Lite Video Recorder/ H.265 Compression

## DVR 5IN1 SYSTEM

AHD /TVI /CVI /CVBS /IPC SYSTEM SUPPORT

# H.265



- 5IN1 Camera System Support
- H.265 Compression
- IPC IP Camera Support
- HDMI Interface
- USB Port
- ONVIF Support
- DDNS
- Cloud
- CMS Support
- Mobile APP

**5MP Lite**  
Video Recorder





# DVR 4000 SERIES

5.0MPixel Lite Video Recorder/ H.265 Compression

## Specification



## Feature

- \* 32 CH TVI / AHD/CVI 5MP/ 4MP/ 3MP / 1080P / 720P WD1 video input
- \* 32 CH DVRs support 8 CH 5MP / 4MP / 3MP / 1080P 960P / 720P IP video input
- \* Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- \* Intuitive and user-friendly Graphics User Interface ( GUI ), window style operation by mouse
- \* Multi-type recording: manual / schedule / sensor / motion analytics recording
- \* Playback : 16 CH simultaneously playback
- \* Search: time slice, time, event, tag and smart search
- \* Express and flexible backup via USB, network and so on
- \* Pentaplex: preview, record, playback, backup and remote access
- \* DHCP, DDNS, PPPoE network protocol
- \* Remote control via Web Client or CMS : preview, playback, backup, PTZ and configuration
- \* Multi-user online simultaneously
- \* Authorization management, log review and device status review
- \* 1080P output, true high resolution display
- \* Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- \* Support NAT function and QRCode scanning by mobile phones
- \* Powerful mobile surveillance by smart phones with iOS and Android OS

# H.265

**5MP Lite**  
Video Recorder



Model	HA-45532H4-V1
Analog Video Input	BNCx32 / BNC interface (1.0Vp-p; 75Ω) TVI/AHD/CVI: 5MP@20fps; 4MP/1080P/720P/WD1@25fps/30fps (live)
<b>Video</b>	
IP Video Input	8CH (up to 24CH) / Up to 5MP@30fps
Total Input	40CH
Output	HDMIx1 : 1920x1080 / 1280x1024 / 1024x768 VGAx1 : 1920x1080 / 1280x1024 / 1024x768 BNCx1 : CVBS (used as the main or spot output)
Compression	H.264 / H.265
Multi-screen Display	1 / 4 / 6 / 8 / 9 / 13 / 16 / 25 / 32 / 36
<b>Audio</b>	
Input	RCAX16
Output	RCAX1 (linear, 600Ω)
Two-way audio	Take up channel one audio input
Compression	G.711(U/A)
<b>Record</b>	
Resolution	5MP Lite/4MP Lite / 1080P/1080P Lite/720P/WD1/D1
Frame Rate	Analog Channel: 5MP Lite@10fps (PAL / NTSC) 4MP Lite/1080P@12fps(PAL) / 15fps (NTSC) 1080P Lite/720P/WD1/D1@25fps (PAL) / 30fps (NTSC) IP Channel: 25fps (PAL) / 30fps (NTSC)
Bit Rate	32Kbps ~ 8Mbps
<b>Playback</b>	
Playback	16CH
Search	Time slice / time / event / tag /smart search
Smart Search	Highlight colors to display the camera record in a certain period of time, different colors refer to different record events
Function	Play, pause, FF, FB, digital zoom, etc.
<b>Alarm</b>	
Mode	Manual, motion, exception, smart event
Input	16CH
Output	4CH
<b>Network</b>	
Interface	RJ 45 1000Mbps x 1
Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, HTTP, HTTPS, NTP, SMTP
Incoming Bandwidth	40Mbps
Outgoing Bandwidth	160Mbps
Client Connection	Max. 10 users access
Mobile Device OS	iOS, Android
<b>Storage</b>	
HDD	SATA x 4, up to 10TB per HDD; E-SATA x 1
Local Backup	U disk, USB mobile HDD
Network Backup	Yes
Port RS 485	Yes (full-duplex), connect to PTZ or keyboard
USB	USB 2.0 x 1; USB 3.0 x 1
Remote Controller	Optional
<b>Others</b>	
Power Supply	ATX-250W
Consumption	≤30W (without HDD)
Dimensions(mm)	440 x 390 x 70 (W x D x H)
Working Environment	-10~50°C, 10%~90% (humidity)