



H5PLUS
Compression

ONVIF



HP-97B602PEL-M

CAMERA 9700 SERIES

Bullet Network Camera





CAMERA 9700 SERIES

Dual Illumination Bullet Network Camera

Specification



Feature

- * H.265+ / H.265 / H.264+ / H.264 / MJPEG coding
- * Max. resolution: 6MP (3200 × 1800)
- * Auto day/night switch
- * 3D DNR, WDR, HLC, BLC, etc.
- * ROI coding
- * Support smart supplement light
- * 10~20m white light view distance;
- * 10~20m IR view distance
- * DC12V/PoE power supply
- * IP 67 ingress protection
- * Support dual streams
- * Support remote monitoring by smart phones& tablet PCs
- * with iOS and Android OS
- * Support line crossing detection & region intrusion detection
- * Support SMD

Model	HP-97B602PEL-M
Image Sensor	1 / 2.7 "CMOS
Image Size	3200×1800
Electronic Shutter	1 / 2s ~ 1 / 100000s
Iris Type	Fixed Iris
Min. Illumination	0.007 lux @F1.6, AGC ON; 0 lux with illuminator on
Lens	2.8mm@F1.6, Horizontal FoV: 110.5°; Vertical FoV: 57°; Diagonal FoV: 131°
Focus	Fixed
Lens Mount	M12
Day&Night	ICR
Wide Dynamic Range	Digital WDR
BLC / HLC / Digital NR	Yes
S/N Ratio	≥50dB
Angle Adjustment	Pan: 0°~360°; Tilt: 0°~80°; Rotation: 0°~360°
Image	
Video Compression	Main stream: H.265+ / H.265 / H.264 + / H.264 Sub stream: H.265+ / H.265 / H.264 + / H.264 MJPEG
H.265 Compression Standard	Main Profile@Level4.1 High Tier
Resolution	6MP(3200×1800), 4MP (2688×1520), 1080P (1920×1080), 720P (1280 × 720), D1, VGA(640×480), 480× 240, CIF
Main Stream	60Hz: 6MP(1~20fps)/4MP/1080P(1~30fps); 50Hz: 6MP(1~20fps)/4MP/1080P(1~25fps)
Sub Stream	60Hz: 720P/D1/VGA/ CIF/480× 240(1~30fps); 50Hz: 720P/D1/VGA/ CIF/480× 240(1~25fps)
Bit Rate	64 Kbps ~8Mbps
Bit Rate Type	VBR / CBR
Audio Compression	G711A/U
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ45



Feature

- * H.265+ /H.265 /H.264+ /H.264/MJPEG coding
- * Max. resolution: 6MP (3200 × 1800)
- * Auto day/night switch
- * 3D DNR, WDR, HLC, BLC, etc.
- * ROI coding
- * Support smart supplement light
- * 10~20m white light view distance;
- * 10~20m IR view distance
- * DC12V/PoE power supply
- * IP 67 ingress protection
- * Support dual streams
- * Support remote monitoring by smart phones& tablet PCs
- * with iOS and Android OS
- * Support line crossing detection & region intrusion detection
- * Support SMD

CAMERA 9700 SERIES

Dual Illumination Bullet Network Camera

Specification

Model	HP-97B602PEL-M
Audio	1CH built-in MIC
Functions	
Remote Monitoring	Web browser /TVT NVR/NVMS2.X/Mobile APP
Web Browser	IE 11 (plug-in required) / Chrome 89.0+ Edge 89.0+/Firefox 87.0+/Safari 14.0+
Online Connection	Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, 802.1x, HTTP
Interface Protocol	ONVIF
Storage	Network remote storage
Motion Detection	Support smart motion detection; filtering motion alarm triggered by other target types except humans.
Smart Event	(Human) region intrusion detection, (human)line crossing detection
General Function	Watermark, video mask, heartbeat
Security	Video encryption, firmware encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP
PoE	Yes, IEEE802.3af
Supplement Light Range	IR range: 10 ~ 20 m; white light range: 10 ~ 20 m
Ingress Protection	IP67
Others	
Power Supply	DC12V/PoE
Power Consumption	< 6W
Operating Environment	- 30 °C ~ 65°C (-22°F~149°F), Humidity: less than 95 % (non-condensing)
Storage Environment	- 30 °C ~ 60 °C (-22°F~140°F), Humidity: less than 95 % (non-condensing)
Dimensions (mm)	167.6 × 75 × 74.6
Weight (net)	Approx. 0.382KG