

5 MPIXEL
DARK FIGHTER

เปลี่ยน ภาพที่งมคืน ให้เหมือนที่งมวัน

HP-30B50PELDK-M
5.0MP Bullet Network Camera



5 ล้านพิกเซล



บันทึกเสียง



รองรับ POE



รองรับภาพสี และขาวดำ



กันน้ำกันฝุ่น

Product Features

- * 5.0 Mega pixel IP Camera
- * Effective Pixels 2880x1616
- * Min. Illumination Color: 0.001Lux
- * 3.6mm / F1.3 Real time H.265
- * Day / Night Auto (ICR) / full Color / B&W
- * Infrared LED 3PCS Smart Dual Light LED
- * Infrared Distance 30M
- * Mic built-in / PoE
- * Protection Level IP66
- * Motion detection
- * Good image, Low price



IPC CAMERA
ความคมชัด **5 MP**

Specifications

Model	HP-30B50PELDK-M
Image Sensor	1/2.7" CMOS Sensor
Pixels	5.0 Mega Pixel
Effective Pixels	2880x1616
Min. Illumination	Color: 0.001Lux
Shutter Speed	Auto: PAL 1/1-1/10000s; NTSC 1/1-1/10000s
Day / Night	Auto (ICR) / full Color / B&W
Wide Dynamic Range	Digital WDR
S/N Ratio	≥52dB
White Balance	Auto
Gain Control	Auto
Backlight Compensation	Off / WDR / BLC / FLK (FlickerControl)
TV System	PAL / NTSC
Lens	
Focus Length	3.6mm
Aperture	F1.3
Focus Control	Fixed
Lens Type	Fixed
Fill Light	
Infrared LED	3PCS Smart Dual Light LED
Infrared Distance	30M
IR Status Under	10 Lux
IR Power	On Lens Auto Contro
Video	
Compression	H.264 / H.265
Image Resolution	Main stream 5MP (2880x1616), 3MP (2560x1440), 2MP (2304x1296) (1920x1080) Sub-stream 448P (800x448) / D1 (640x360) / CIF (352x288)
Frame Rate	5MP 25Fps
Bitrate Control	VBR / CBR
Dual-stream	Supported



IPC CAMERA
ความคมชัด **5 MP**

Specifications

Model	HP-30B50PELDK-M
Digital Noise Reduction	3D noise reduction
Image Control	Saturation, Brightness, Contrast, Sharpness, Mirror
Privacy Masking	3 Rectangular Zone
Audio	
Audio Compression	G.711
Audio input	Mic built-in
Network	
Network Protocols	ONVIF, P2P, CGI, HTTP, TCP/IP, IPv4, RTSP, UDP, NTP, DHCP, DNS, IP Filter
User Interface	Web, App (iOS, Android)
Application Programming	ONVIF2.4, RTSP
Video Delay	0.3S (Within the Lan)
Intelligent Functions	
Motion Detection	Supported
External Interfaces	
Network	10/100M, RJ-45 interface
Audio input	Mic built-in
Operation Environment	
Operating Temperature	-10°C ~ +50°C RH95% Max
Operating Humidity	-20°C ~ +60°C RH95% Max
Protection Level	IP66
Electrical	
Power	DC12V±10%, 1000mA
POE	Supported
Mechanical	
Weight	0.6kg
Dimension	204.28 * 64.61 * 69 * 17 mm
Housing	Metal