




HS-SW20 2P16 S2 HBT-AI

Product Features

- * Total 240W Power Supply
- * 16 ports PoE
- * 2 ports Uplink
- * 2 ports SFP
- * AI Watchdog Function
- * 6KV Lightning & 8KV ESD Protection
- * Support bt 60W High Power

Ports Description



- 1 100Mbps PoE
- 2 100Mbps bt 60W PoE
- 3 1000Mbps Uplink
- 4 1000Mbps SFP

Model: HS-SW20 2P16 S2 HBT-AI Specifications



Ports	PoE (1~14):10/100Mbps PoE ports (RJ45) PoE (15~16):10/100Mbps PoE ports,Support bt 60W High Power
	LAN (17~18):10/100/1000Mbps uplink ports (RJ45) SFP (19~20):10/100/1000Mbps SFP port
Transmission Rate	2000Mbps Full Duplex; 10 or 100Mbps Half Duplex
Transmission Distance	Port1~15: 10/100Mbps 130meters; 10Mbps Auto-adaption 250meters / Port16: 10/100Mbps 130meters
Performance Specification	Bandwidth:11.2Gbps / MAC address table: 8K Network Latency (1000Mbps): $\leq 16\mu s$ (use the 64byte package size) The Frame Filter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port;1488000pps the most for 1000M port
Networking Standard	IEEE 802.3i 10BASE-T/IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T / IEEE 802.3x Flow Control IEEE 802.3af/at/bt Power over Ethernet
Power Support	Power Input: AC 90~240V Total $\leq 240W$ / AI Watchdog: Port 1~16 Power Output: PoE1~14 Port:1/2(+52V),3/6(GND) $\leq 30W$ PoE15~16 Port:1245(+52V),3678(GND) Compatible1/2(+52V),3/6(GND) $\leq 60W$
Protection Level	Lightning Protection:6KV / ESD Protection:8KV
Physical Specifications	Size(L*W*H): 440mm*180mm*45mm, Weight: 2.42KG
Working Environment	Operating Temperature: -30°C~60°C / Storage Temperature: -40°C~70°C Operating Humidity: 10%~90% Non-condensing Storage Humidity: 5%~90% Non-condensing