



10^{L2}
PORT

8 × 10/100/1000 Mbps RJ45 (PoE)
2 × Gigabit SFP Uplink

L2 Managed PoE Switch



PROTECTION, RELIABILITY
ELECTRIC SAFETY



MAC Address Table



IEEE 802.3af/at
Standard



Plug & Play



PD Alive



VLAN



Loop
Protection

Specifications

Model : HR3200-10P

Standard	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3x, IEEE 802.1X, IEEE 802.1q, IEEE 802.1p, IEEE 802.1d, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at
Network Media (Cable)	10BASE-T: UTP category 3,4,5 cable (≤100m) 100BASE-TX: UTP category 5, 5e cable (≤100m) 1000BASE-T: UTP category 5e, 5 cable (≤100m) 1000BASE-X: MMF, SMF
MAC Address Table	8K, Auto-learning, Auto-aging
Jumbo Frame	9216 Bytes
Packet Buffer	4.1 Mbit
Transfer Mode	Store-and-Forward
Switching Capacity	20Gbps
Packet Forward Speed	14.88Mpps
Dimensions (L*W*H)	220 × 150 × 44 mm
Fan Quantity	1
Input Voltage	AC 100-240V 50/60Hz
PoE Output	30W Max./Port
PoE Power Budget	120W
Power Supply	130W
Operating Temperature	0°C ~ 50°C
Storage Temperature	-40°C ~ 70°C
Operating Humidity	10% ~ 90% non-condensing
Storage Humidity	5% ~ 90% non-condensing
Web Management	Supported
LED Indicators	PWR / DATA / PoE

Key Features

- ✓ 8 × 10/100/1000 Mbps RJ45 (PoE)
- ✓ 2 × Gigabit SFP Uplink
- ✓ L2 Managed PoE Switch
- ✓ IEEE 802.3af/at Standard
- ✓ VLAN / QoS / Storm Control
- ✓ DHCP Snooping / Port Isolation / MAC Filter
- ✓ PD Alive (Auto Reboot Camera)
- ✓ Loop Protection

Application Diagram



Stable & Reliable
เสถียรภาพสูง



Easy Management
บริหารจัดการง่าย



CCTV Optimized
เหมาะสำหรับงานกล้องวงจรปิด