





HV-Amplifier horn 30 W

Product Specification

(1/2)

Rated Power	30 W
Maximum Power	40 W
Sound Pressure Level (SPL)	112 ± 3 dB @ 1 W/1 m, 1 kHz
Rated Frequency Range	300 Hz – 5.5 kHz (-20 dB band)
Resonance Frequency	700 Hz ± 15% @ 1 V, 25°C
Total Harmonic Distortion (THD)	≤ 5% @ 1 kHz, 1 W
Rated Impedance	8 Ω
Power Supply	DC 12–24 V,
	2 A
Audio Connection	3.5 mm audio connection
NVR/DVR Connection	RCA connection via supplied adapter
Volume Control	Built-in rear volume control for on-site adjustment
Ingress Protection	IP65



HV-Amplifier horn 30 W

Product Specification

(2/2)

Horn Material	ABS
Mounting Bracket	Stainless steel U-bracket
Finish	White
Dimensions (W × H × L)	285 × 205 × 280 mm
Net Weight	2.1 kg ± 10%
Mounting Holes	3 × Ø11 mm
Mounting Hole Spacing	100 mm center-to-center
Operating Temperature	-20°C to +40°C
Relative Humidity	45%–85% RH
Installation Altitude	Below 1,000 m
Power Cable Extension	Up to 100 m total length
Cable Length Note	Excessive cable length may affect sound quality and output volume.